

**SF12L PIII
HIGH TEMPERATURE IMAGING SYSTEM
SPECIFICATIONS**

SYSTEM INCLUDES:

- High resolution, solid state thermal imaging camera
- Air-cooled stainless-steel furnace lens with Bright Image Optical System™
- IP66/NEMA 4X camera housing with manual slide trac mount (tripod base for portable system)
- Quick change back plate
- 12 VDC power supply with IP66/NEMA 4X Enclosure and 15 ft. (4.5 m) power cord
- Regulator assembly with 2 ea. 15' (4.5 m) quick disconnect air lines
- Factory assembled, pre-adjusted and ready for installation

CAMERA:

Sensor: LWIR
Video: RS170 or CCIR
Power: 12 VDC with 100 - 240 VAC adapter - 50/60 Hz

LENSES:


Overall length: 8" or 18" (5.5" and 15" usable length) Straight Ahead Line of Sight
Diameter: 1.650" (42 mm)
Field of view: See Lens Selection Guide
Angle of view: Straight ahead (standard)
Temperature: Scenes being monitored to 3500° F (1927° C)
Air Purge: 15-25 psig @ 20-40 scfm - straight ahead line of sight lens (**application dependent**)
Instrument quality air only T<100°F (40°C)

ENCLOSURE:

Material: PHASE III = **STEELON™** (stainless steel over high temperature synthetic)
Temperature: Ambient temperatures to 550° F [289° C] (with optional accessories)
Air purge: 3-10 psig @ 3-10 scfm (**application dependent**)
Instrument quality air only
77°F (25°C) <T< 122°F (50°C)

OPTIONS AND ACCESSORIES INCLUDE:

- SAM0007-XX or SAM0012-XX wallbox mount
- MSS0010C automatic retract
- Video monitor
- Automatic Port Deslagger
- Quick-change Lens
- SAM0009 or SAM0028 air filtration system
- Video recording
- Coaxial cable or fiber optic transmission system
- **PYROVIPER™** thermal imaging software



**SYN-FAB's SF12 series infrared imaging systems are subject to US export regulations and may require a license prior to export.
Diversion contrary to US law is prohibited.**



7863 SCHILLINGER PARK ROAD • MOBILE, ALABAMA 36608 • USA
PH: (251) 633-4942 • FX: (251) 633-2514 • E: info@synfab.com

09/2026